



PRODUCT INFORMATION

JUNE 2018



D50

Alemlube Diesel Driven 2" Diesel & Water Transfer Engine Pump

The Alemlube D50 diesel driven 2" transfer engine pump is specifically designed and manufactured for the transfer of diesel and water. Mounted in a robust tubular steel roll frame with rubber feet the D50 is completely portable, suits many industrial, workshop, agricultural, municipal, marine services and on site applications including construction site dewatering and is capable of transferring up to 500 litres of diesel fuel or water per minute.

Driven by a powerful diesel engine this lightweight die-cast aluminium pump with 2" diameter inlet & outlet ports operates efficiently with a maximum suction head of 7 metres and a maximum lift head of 28 metres.

Always ready to perform tank filling, diesel or water transfer the D50 has a 2.5L fuel tank capacity with a manual starting system.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

- Flow rates of up to 500L/min
- 4.0HP (3,600rpm) air cooled 4-stroke diesel engine
- 2" (50mm) inlet/outlet
- Maximum suction head of 7m
- Maximum lift head of 28m
- Fuel tank capacity of 2.5L
- Oil tank capacity of 0.75L
- Completely portable with pull start

ORDERING INFORMATION

D50 Alemlube Diesel Driven 2" Diesel & Water Transfer Engine Pump

