



PRODUCT INFORMATION

October 2016 Update



50090 240V High Flow Diesel Fuel Bowser

The 50090 240V high flow diesel fuel bowser is designed and produced in Italy for non-commercial use and its sturdy structure allows fixing to walls, tanks and drums. A specially manufactured pedestal is available for a free standing bowser type application, model number 50090P including pedestal complete.

Capable of flow rates of up to 90 L/min the 50090 bowser is supplied standard with an automatic nozzle with swivel connection and four metres of 1" diesel fuel hose.

The pump at the heart of the 50090 is a self-priming vane type pump fitted with a bypass and is installed on anti-vibration supports, effectively prolonging service life. A nutating disk displacement flow meter with 4-digit mechanical readout system is extremely accurate and reliable.

A compact and space saving design incorporates an integrated nozzle holder with stop/start pump lever, intake mesh filter and an induction motor that is fitted with thermal motor overload protection.

The 50090 240V high flow diesel fuel bowser is a significant and sought after new addition to the premium Alemlube bowser range.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Automatic nozzle with flow rates of up to 90 L/min

Self-priming vane type pump

Induction motor fitted with thermal motor overload protection

Intake mesh filter

Accurate to $\pm 1.0\%$

IP55 Rating


Duty Cycle 30 minutes on, 30 minutes off

700 watt

4.9 Amp maximum

Noise level below 75 dB

1" diesel fuel hose length of 4m



ORDERING INFORMATION

50090 240V High Flow Diesel Fuel Bowser

50090P 240V High Flow Diesel Fuel Bowser with Pedestal

