



PRODUCT INFORMATION

August 2016

223003 Alemlube 205L Mobile Grease Transfer Kit

The Alemlube 223003 is a 205L mobile grease transfer kit consisting of a 55:1 ratio air operated grease transfer pump (409200) capable of delivery rates of up to 300 g/min, a durable Alemlube S Series grease hose reel supplied complete and ready to use with 10m x 6mm ID delivery hose (SG800) with Samoa control valve (413080) and a heavy duty 205L drum trolley with two robust solid wheels plus two swivelling rear wheels ensuring ease of movement, stability and safety.

The 223003 is an economical, quality mobile grease transfer kit providing workshop flexibility by facilitating quick, efficient and effortless grease transfer in car, light commercial vehicle and truck & bus workshops.

The Samoa 55:1 pressure ratio pump has an air pressure operating range of 20 to 140 psi and is ideal for the transfer of grease up to NLGI2 specification.

The grease hose reel is manufactured from high quality impact resistant and UV stabilised polypropylene, features a positive latching system, heavy duty internal spring assembly and highly flexible S.A.E.100 R2 rubber hose with crimped hose ends.

The Samoa grease control valve is the perfect device at the end of the hose assembly to control grease delivery. Its lightweight ergonomically designed aluminium body delivers reliable performance in all applications.

PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Transfer kit delivery rates of up to 300 g/min

Suits 205L drums

Impact resistant heavy duty hose reel

10m x 6mm ID delivery hose

0.9m lead in hose

Maximum fluid outlet pressure of 7,700psi (550 bar)

Samoa grease control valve with rigid outlet

Heavy duty trolley with robust solid wheels



ORDERING INFORMATION

223003

Alemlube 205L mobile grease transfer kit with grease control valve

