



PRODUCT INFORMATION

November 2015

30080

Mobile Waste Oil Drainer

The 30080 mobile waste oil drainer available from Alemlube has a holding tank capacity of 80L and is designed to safely transfer and capture waste oil from engine crankcases, transmissions and differentials. The 30080 mobile waste oil drainer is easy to use and the waste oil can be emptied from the machine with the aid of air pressure. With its height adjustable oil reservoir, minimum height 1280mm / maximum height 1940mm, the 30080 is suitable for use in a variety of workshop applications and is equipped with a pneumatic safety relief valve that has been factory calibrated at 1 bar (14psi). Covered by a one year warranty the 30080 mobile waste oil drainer from Alemlube is sure to provide years of reliable service.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Transfers and captures waste oil from crankcases, transmissions and differentials

Holding tank capacity of 80L

Height adjustable waste oil reservoir - min 1280mm / max 1940mm

Reservoir oil level gauge indicates the drained oil quantity

Holding tank emptied with the aid of air pressure

Equipped with a pneumatic safety relief valve calibrated at 14psi

12 month warranty

- | | |
|-----------------------------------|-------------------------------|
| 1 Metal collection bowl extension | 8 Pressure gauge |
| 2 20L capacity collection bowl | 9 Audible filling level alert |
| 3 1" telescopic tube | 10 Pneumatic emptying hose |
| 4 Telescopic tube handle | 11 Rubber wheels |
| 5 Rubber covered handle | 12 Ball bearing wheels |
| 6 Parts and accessory tray | 13 Highly manoeuvrable |
| 7 Patented safety valve | 14 80L capacity holding tank |

ORDERING INFORMATION

30080
Mobile Waste Oil Drainer