



## PRODUCT INFORMATION

November 2015



# 5080AN Hi Flo Refuelling Drum Pump with Filter

The 5080AN hi flo refuelling drum pump with filter has low torque, is easy to use and with little effort is capable of delivering up to 110 litres per minute or best in class delivery rates of 1.1 litres per rotation.

Supplied complete with an FA2 fuel filter, 2.6 metres of antistatic, UV & fuel resistant hose, spout, in built spout holster, 3-piece downtube and new heavy duty bung adaptor, the 5080AN also features a PPR covered handle grip designed to reduce operator fatigue during high volume fuel transfer. The FA2 fuel filter features a 10 micron fuel filter element, a drain cock and a replaceable clear plastic bowl and a 1" BSP inlet and outlet.

Suitable for the fast and efficient transfer of diesel fuel, petrol, light oils up to SAE30 and kerosene the 5080AN incorporates a lockable handle to help minimise the possibility of unauthorised fuel transfer.



### PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Low torque, high volume easy to use pump delivers up to 110 L/min

Delivery rates of 1.1 litres per rotation

Lockable handle minimises the possibility of unauthorised fuel transfer

New PPR covered handle grip reduces operator fatigue

New and improved rubber seal above the bung adaptor reduces fuel contamination

Supplied complete with 2.6m of UV and fuel resistant hose, spout, in built spout holster, 3-piece downtube, heavy duty bung adaptor

FA2 fuel filter features a 10 micron fuel filter element, a drain cock and a replaceable clear plastic bowl with a 1" BSP inlet and outlet

Steel springs on the hose assembly reduce the possibility of premature hose failure

Suitable for the transfer of diesel fuel, petrol, light oils up to SAE30 and kerosene

Also available 5060AN without FA2 fuel filter

### ORDERING INFORMATION

#### 5080AN

Hi flo refuelling drum pump with filter

