



PRODUCT INFORMATION

January 2015



DWFF20500

Diesel Driven 2" Fire Fighting Pump

The Alemlube DWFF20500 petrol driven 2" fire fighting pump is specifically designed and manufactured for the transfer of water. Mounted in a robust tubular steel roll frame with rubber feet the DWFF20500 is completely portable, suits many agricultural, municipal, marine services and on site fire fighting applications and is capable of transferring up to 466 litres of water per minute. Driven by a powerful 5.5HP air cooled 4-stroke diesel engine this lightweight die-cast aluminium pump with 2" diameter inlet & outlet ports operates efficiently with a maximum suction head of 7 metres and a maximum lift head of 45 metres. Always ready to perform in emergency and property protection operations, the DWFF20500 has a run time of 2.0 hours at ¾ load, a 3.5L fuel tank capacity and is available with pull start or key start ignition.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Flow rates of up to 466L/min

5.5HP air cooled 4-stroke petrol engine

2" (50mm) inlet & outlet ports

Fuel tank capacity of 3.5L

Recoil starting system

Run time (per tankful) at ¾ load of 2.0 hours

Maximum lift head of 45m

Maximum suction head of 7m

Dimensions: 535mm x 455mm x 545mm

Dry weight: 56kg

Pull start or key start ignition

DIESEL DRIVEN FIRE FIGHTING PUMPS AVAILABLE

DWFF15300	1-1/2"	Pull Start	300 L/min
DWFF20500	2"	Pull Start	466 L/min
DWFF301000	3"	Pull Start	633 L/min
DWFF15300KS	1-1/2"	Key Start	300 L/min
DWFF20500KS	2"	Key Start	466 L/min
DWFF301000KS	3"	Key Start	633 L/min

ORDERING INFORMATION

DWFF20500
Diesel Driven 2" Fire Fighting Pump

