



PRODUCT INFORMATION

FEBRUARY 2017



BEKATWO-250

Single Point Grease Lubricator

SEALED FOR LIFE
REFILLABLE
REUSABLE
DISPOSABLE

The BEKATWO-250 is a fully sealed, electro-mechanical single point grease lubricator with 250 gram capacity that can be refilled in the field up to six times before disposal.

The unique BEKATWO-250 design allows the user to fill the lubricator with grease of their own choice and to choose a desired discharge rate. This flexibility permits the use of any grease and eliminates the need for custom cartridge filling. It also means that consumable costs are reduced because grease cartridges and batteries are no longer required – simply refill the BEKATWO-250 via the grease nipple.

With a capacity of 250 grams and a battery lasting for 6 complete discharges or 36 months, the BEKATWO-250 dispenses a total of up to 1,500 grams of grease before needing to be replaced.

Maximum operating pressure is a class leading 10bar which allows for remote mounting up to a distance of 2m and the use of bearings which have higher inlet pressures.

Completely sealed, the BEKATWO-250 can be switched on or off at any time, and the discharge rates adjusted from 1, 3, 6, 12 or 24 months via a magnetic cap and reed switch system.

The user is given clear status indication via red and green LEDs which show the discharge rate setting, the battery level and a high pressure blockage alarm.

Manufactured in Germany, the BEKATWO-250 offers high precision and reliability with extremely low running costs in comparison to other single point lubricators on the market today.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Flexibility to operate and refill with the grease of your choice

No grease cartridges or batteries required

Class leading 10 bar maximum pressure allows for remote mounting up to 2m

IP65 protection class. Temperature range from -20°C to +60°C

250gm capacity (6 x 250gm = 1,500gm total before replacement)

Battery life is 6 refills or 48 months (whichever comes first)

Discharge rates adjustable from 1, 3, 6, 12, 24 months

Red LED indication for blockage alarm

Green LED indication for discharge rates and battery status

1/4" BSP thread

ORDERING INFORMATION

BEKATWO-250 Single Point Grease Lubricator

Also available: **BEKAONE-120** Single Point Grease Lubricator (120gm capacity)

